

VACUUM SINGLE CHAMBER

Models | 400 | 450A | 450T | 550A | 560A | 580A

HEAVY-DUTY

This high-quality, user-friendly, and easy to clean machine integrates heavy-duty parts, thereby providing great reliability.

PERFORMANCE

This model is designed to package large volumes of oversized products. The modified atmosphere packaging (MAP) option increases the product's shelf life, provides extra protection, prevents colouring.

CERTIFIED

The Sipromac vacuum packaging machines are ETL LISTED, CSA certified and conform to UL STD. They are designed for easy cleaning and comply with the industry's highest hygiene and food safety standards.

WHY SHOULD YOU VACUUM PACK ?

- 1 To reduce spoilage by removing air from the package resulting in much longer shelf life;
- 2 To prevent dehydration;
- 3 For ease of handling;
- 4 To slow down oxidation;
- 5 To protect against external contamination.



MODELS 400, 450A AND 450T

		400	450A	450T
SEAL BARS	Length	A 19.1" (485 mm)	19.1" (485 mm)	19.1" (485 mm)
	Qty	2	2	2
	Distance between	B 23" (584 mm)	23" (584 mm)	22" (559 mm)
CHAMBER DIMENSIONS	Height	9.5" (241 mm)	9.5" (241 mm)	8" (203 mm)
BUSCH PUMP	Std.	40 m ³ 2.0 HP	40 m ³ 2.0 HP	20 m ³ 0.9 kW
MACHINE DIMENSIONS	Width	E 30.5" (775 mm)	30.5" (775 mm)	30.5" (775 mm)
	Depth	F 32" (813 mm)	32" (813 mm)	28" (711 mm)
	Height	G 44" (1,118 mm)	44" (1,118 mm)	21" (533 mm)
POWER SUPPLY		208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	120 V / 1 pH / 60 Hz
MICROPROCESSOR		MC-05	MC-40	MC-40

VACUUM SINGLE CHAMBER

Models | 400 | 450A | 450T | 550A | 560A | 580A




MODELS 550A, 560A AND 580A

		550A	560A	580A
SEAL BARS	Length A	26" (660 mm)	26" (660 mm)	33.5" (855 mm)
	Qty	2	2	2
	Distance between B	23.25" (591 mm)	31" (787 mm)	36.75" (933 mm)
CHAMBER DIMENSIONS	Height	8" (203 mm)	8" (203 mm)	8" (203 mm)
BUSCH PUMP	Std.	63 m ³ 3.0 HP	100 m ³ / 5,0 HP	165 m ³ 7.5 HP
MACHINE DIMENSIONS	Width E	31" (787 mm)	38" (965 mm)	45.25" (1,153 mm)
	Depth F	36" (914 mm)	36" (914 mm)	46.5" (1,183 mm)
	Height G	47" (1,194 mm)	47" (1,194 mm)	43.75" (1,113 mm)
POWER SUPPLY		208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-40	MC-40

2 SEAL BARS

MC-40

MC-05



BASIC FEATURES

- Single chamber
- Stainless steel construction
- Twin seal element – Double seam band
- Vacuum sensor - Vacuum level controlled in percentage, directly with Microprocessor (except model 400)
- Filler plates
- Cover latch
- Wheels (stainless steel)
- Rear panel
- Crate
- Certification: ETL listed C & US (CSA & UL) (except model 400)

OPTIONAL FEATURES

- Electric cut-off - Two wire seal system: outside wire cuts off excessive part of bag
- Bi-active seal - Sealing from top and bottom for thick pouches and aluminum bags on models 550A, 560A and 580A
- Modified atmosphere packaging (MAP) - Increases the product's shelf life, provides extra protection, prevents colouring (except model 400)
- Air regulator – Regulates air pressure in the seal bars bladders with compressed air (not included) (except model 400)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- 12" (305 mm) chamber lid on models 550A, 560A and 580A
- Vacuum pump sizes
- Stainless steel tilted insert for liquid products
- Silencer
- Other voltages available
- Heated control box for microprocessor
- Service kit for standard maintenance

All features are subject to change without notice.